

SPECIFICATIONS

DESCRIPTION:

Compact LED accent fixture. Suitable for wet/damp/dry location installations.

MATERIAL:

Standard overall material is 6061 aluminum.

FINISH:

- AA - Anodized Satin Aluminum
- AP - Powder Coat Aluminum
- BK - Powder Coat Black
- BZ - Powder Coat Bronze
- WT - Powder Coat White

LED OPTIONS

Integral high output LED, warm white 85 CRI (90 available)

2700K or **3000K** Standard (**4000K**, **5000K**, & **6000K** available)

1LED - 1W (42 lumens)

Optics

- SP - Spot, 12°
- NF - Narrow Flood, 24°
- FL - Flood, 36°

VOLTAGE:

Driver - 350mA output driver required, not included.

MOUNTING:

Fixture is designed with a fixed 1/2-NPS mount.

OPTIONS:

Glare shields

GL-1 - Angled, aluminum

GL-3 - Straight, aluminum

Lenses/Louvers/Color Filters

LA-1-8 - Hexcell Louver (Black)

LA-2-8 - Prismatic lens

LA-3-8 - Linear spread lens

LA-4-8 - Soft focus lens (diffused)

LA-5-8 - Moonlight lens

LA-6-8 - Blue lens

LED Constant Current Drivers

HLD-3-350-12 - 3W 350mA 12VAC driver

HLD-3-350-U - 3W 350mA 120-277VAC driver

See fixture accessories for more information.

SAMPLE ORDER SPECIFICATION:



HL-306-LED-AA-GL-3-LA-5-8

RATING:

Wet/damp/dry location.



MADE IN THE USA



ORDER SPECIFICATION: _____ - _____ - _____ - _____ - _____
 Fixture Finish Lamping Voltage Options/Access.

PROJECT:

APPROVED:

NOTE:

TYPE:



HEVI LITE, INC.

9714 Variel Ave, Chatsworth, CA 91311
 Tel., (818) 341-8091 - Fax (818) 998-1986
 Web Site <http://www.hevilite.com>

CATALOG NUMBER:

HL-306-LED

Driver Options




HLD-3-350-12

Compact dimmable 12-Volt / 350mA constant current LED driver for 1-3W LEDs.
Driver is dimmable standard with MLV TRIAC dimmer.




HLD-3-350-U

Compact universal voltage (100-277v) 350mA constant current LED driver for 1-3W LEDs. Non-dimmable.




HLD-CBB

Direct burial composite enclosure with (1)LED driver and (1)fixture mount location.
Enclosure comes standard with junction compartment and anti-siphon chamber ensures no water can enter the main housing.




H-POD-LED

Direct burial LED Driver pod with (1) driver. Pod is equipped with moisture-lock cords to prevent water wicking.
Suitable for wet/damp/dry location installation.



H-POD-LED-2X

Direct burial LED Driver pod with (2) LED drivers. Pod is equipped with moisture-lock cords to prevent water wicking.
Suitable for wet/damp/dry location installation.




HL-RD

3R rated rain tight stainless steel enclosure with (1) LED driver. Suitable for wet/damp/dry location installations.


HL-RD-2X

3R rated rain tight stainless steel enclosure with (2) LED drivers. Suitable for wet/damp/dry location installations.




SMED

Surface mount canopy with (1) LED driver, for (1) fixture. Suitable for wet/damp/dry location installations.



WMED

Wall mount canopy with (1) LED driver, for (1) fixture. Suitable for wet/damp/dry location installations.



GM-9-LED

LED driver in PVC landscape post/mounting spike for ground mounting applications.
Suitable for wet/damp/dry location installations.