SPECIFICATIONS

DESCRIPTION:

Wall mount Up/Down MR16 accent fixture. Suitable for wet/damp/dry location installations.

MATERIAL:

Standard overall material is 6061 aluminum. HL-340-2X - Machined Aluminum (Standard) HL-340-2X-2b - Machined Brass

FINISH:

- AA Anodized Satin Aluminum AP Powder Coat Aluminum BK Powder Coat Black

- BZ Powder Coat Bronze
- WT Powder Coat White
- N Natural, for Stainless Steel and Brass

HALOGEN LAMPING OPTION:

Lamp Type - 12V halogen MR16 lamp, bi-pin GX5.3 base, 50W max, not included (standard).

LED OPTIONS:

Integral high output LED, warm white 85 CRI (90 available) 2700K or 3000K Standard *(4000K, 5000K, & 6000K available)*

- **3LED** 3W LED 180 lumens **8LED** 8W LED 300 lumens
- 8LED-E 8.4W LED 565 lumens

OPTICS

- 3LED and 8LED: SP - Spot, 12° NF - Narrow Flood, 24° FL - Flood, 36° 8LED-E: SP - Spot 14° NF - Narrow Flood, 25°
- MF Medium Flood, 30° FL Flood, 40°

VOLTAGE: 12 - 12 VAC output transformer required,

MOUNTING:

Fixture is equipped with a 4.75" mounting plate and (2) mounting screws.

OPTIONS: Glare shields GL-10 - Short Angled, aluminum GL-11 - Angled, aluminum GL-12 - Angled, brass GL-13 - Straight, aluminum GL-14 - Straight, brass Ø4 3/4" [121] Lenses/Louvers/Color Filters LA-1 - Hexcell Louver (Black) LA-2 - Prismatic lens LA-3 - Linear spread lens 8 9/16 LA-4 - Soft focus lens (diffused) [217] LA-5 - Moonlight lens LA-6 - Blue lens See fixture accessories for more information. RATING: Wet/damp/dry location. 3 3/8" ► [86] MADE IN THE USA Intertek ORDER SPECIFICATION: Fixture Voltage Options/Access. Finish Lamping PROJECT: HEVI LITE, INC 9714 Variel Ave, Chatsworth, CA 91311 APPROVED: Tel., (818) 341-8091 - Fax (818) 998-1986



0

Ø2 1/4"

[57]

TYPE:

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF HEVI LITE, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF HEVI LITE, INC. IS PROHIBITED.