SPECIFICATIONS

DESCRIPTION:

High output wall mount LED accent fixture. Suitable for wet/damp/dry location installations.

MATERIAL:

Standard overall material is 6061 aluminum.

FINISH:

AA - Anodized Satin Aluminum
AP - Powder Coat Aluminum
BK - Powder Coat Black
BZ - Powder Coat Bronze WT - Powder Coat White

LED OPTIONS:

LED OF ITOMS:
Integral high output LED module.
LED Output
L30 - 11.6W, 350mA, 1090 Lumen
L35 - 15.5W, 500mA, 1450 Lumen
L40 - 25.4W, 700mA, 2055 Lumen
Color Temperature CCT 27 - 2700K CCT 30 - 3000K CCT 35 - 3500K CCT 40 - 4000K CCT Reflector, Field Replaceable SP - Spot, 17° NF - Narrow Flood, 24° FL - Flood, 36°

XIC - XICATO LED option available.

WFL - Wide Flood, 60°

VOLTAGE:

Requires remote LED driver. 120V Leading edge/trailing edge dimmable. 277V dimmable in 0-10V only. Constant current remote LED Driver included. See driver options. **120-277 -** 120-277V LED driver 120-277-010 - 120-277V 0-10V Dimming Driver

Fixture includes HL-RD remote LED driver enclosure (3R rated stainless steel enclosure) standard. Driver options available in place of HL-RD for direct burial, surface, ground and wall

mounting available.

H-POD-LED-L** - Remote direct burial driver.

HL-XLD-L** - 40-240 Watt remote driver.

SMED-L** - Surface mount driver canopy.

WMED-L** - Wall mount driver canopy.

MOUNTING:

Fixture is equipped with a 4.75" dia. mounting plate and (2) mounting screws.

OPTIONS:

OPTIONS:
Glare shield
GL-920 - Angled, aluminum
GL-921 - Straight, aluminum
GL-922 - Align Angle, aluminum
Lenses/Louvers/Color Filters
LA-1-920 - Hexcell Louver (Black)
LA-2-920 - Prismatic lens
LA-3-920 - Linear spread lens
LA-4-920 - Soft focus lens (diffused)
See fixture accessories for more informatic See fixture accessories for more information.

SAMPLE ORDER SPECIFICATION:

HL-352-BZ-L40-30-FL-120-277-SMED-L40


HL-352 is listed and waranteed only for use with HL-Drivers. See driver options above.


RATING:


Wet/damp/dry location.




MADE IN THE USA









ORDER SPECIFICATION: _	-	- _ Finish	LED Options	Voltage	- Options/Access.
PROJECT:			HEVI LITE, INC.		
APPROVED:			9714 Variel Ave, Chatsworth, CA 91311 Tel., (818) 341-8091 - Fax (818) 998-1986 Web Site http://www.hevilite.com CATALOG NUMBER:		
NOTE:					
TYPE:				HL-3	52